

National Declaration of Performance

Façade ladder

- 1 Construction product's designation and trade name:
Product kit for Installation of fixed façade ladder according to the system: Façade ladder
- 2 Construction product type designation(s) per constituent component:
- Roof/façade ladder 1.5 m / 2.4 m
 - Extension, roof/façade ladder
 - Bracket kit A-220 / A-400 / A-500 / A-600 / A-800 / A-1000
 - Mounting plate, façade ladder
 - Handrail for façade ladder 1280 mm
 - Foldable landing, façade ladder, compl. 390 x 410 mm
 - Steel plate façade ladder excl. screws 300 x 440 mm
 - Bracing kit for handrail adjustable
 - Transition safety rail façade to roof
 - Safety rail 300 1.2 m
 - Bracket, safety rail
 - Extension safety rail
 - Runner, safety rail
 - End plug kit
- 3 Construction product's intended use:
- Access route to the roof via the façade
 - Attachment of personal fall protection equipment
 - Anchoring of personal fall equipment in the rail system
 - Landing, foldable
 - Standing platform
 - Installation of intended façade types according to specification page 2
- 4 Manufacturer's name and contact address
CW Lundberg Industri AB - Landsvägen 52, Box 138, 792 22 Mora, Sweden
- 5 Authorised representative if such has been appointed:
CW Lundberg Sp. z o.o. - ul. Strefowa 9, 58-200 Dzierżoniów, Polska
- 6 Assessment and inspection of performance:
Assessment and ongoing inspection are conducted by the supervisory body, as well as through in-house inspections.
- 7 Technical specification:
Accredited certifying body 0402 RISE, Research Institutes of Sweden
Certificate 12 71 01
Applied technical specifiation: SS 831340

- 8 Construction product performance:

Essential characteristics	Performance	Remarks
Mechanical strength - Static load (according to 6)	Fulfils	-
Dimensions (according to 4)	Fulfils	
Corrosion resistance (according to 7)	Fulfils	

- 9 Performance for the aforementioned product complies with the product performance as indicated in Section 8. This document is issued at the manufacturer's own responsibility according to Section 4.

Signed on behalf of the manufacturer by:



Thomas Lundberg
Managing Director
Mora, 30 April 2024



The product information stated below does not constitute a part of the declared product performance. The manufacturer provides additional information about the product that affects or may affect its use.

Installation of façade ladder on wooden and sheet metal façade performed in accordance with installation instructions M-130. For other façade materials, use screw joints that are suitable for the façade's conditions in accordance with M-302.

Products can be selected in various colours of powder coating for design.

Other Performance

<i>Properties</i>	<i>Performance</i>	<i>Technical specifications</i>
Corrosion resistance (corrosivity class C4)	40 years	EN ISO 12944-2
Exterior reaction to fire (according to 7.3)	B _{roof}	EN 516:2006